

Aluminum Adjustable Height Gantry Crane with Pneumatic Rubber Casters 10 Ft. Wide x 10 Ft. Max Usable Height 4,000 Lb. Capacity Silver

MODEL AHA-4-10-10-PNU

Overhead Lifting / Adjustable Height Aluminum Gantry Cranes with Pneumatic Casters

PRODUCT OVERVIEW

The adjustable height Aluminum Gantry crane combines a lightweight, rigid, and sturdy construction into one unit. The all aluminum construction of this gantry crane makes it corrosion resistant and perfect for outdoor use. Included are two (2) straps, allowing the gantry crane to be transported in one neat package.

KEY FEATURES

- Heavy-duty welded aluminum construction
- Pinned connections for quick set up and take down
- Easily adjustable height with fork truck or other overhead lifting device
- Smooth rolling with four double pneumatic rubber casters



CORE PRODUCT DATA

ASSEMBLED WEIGHT
498 lbs

ASSEMBLED SIZE
72.8125" W x 125.625" L x 139.25" H

SHIP WEIGHT
699 lbs

PACKAGE 1 SIZE
29" W x 120" D x 20" H

COLOR / FINISH
Silver

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lbs)	4,000
Overall I-Beam Length (ft.)	10
I-Beam Height (In.)	8
I-Beam Flange Width (in.)	4-3/16
Under I-Beam Range (in.)	101-1/4 to 131-1/4
Base Width (in.)	72-13/16
Caster Quantity/Diameter/Width (in.)	(4) 15-1/2 x 5-7/8
Caster Type	(4) Swivel
Caster Material/Color	Pneumatic Rubber
Caster Top Plate (in.)	4x4.5 w/ adaptor plate
Usable Trolley Travel Distance (in.)	96.25
Increment Height Adjustment (in.)	6
Standards	B30.17
Compliance	OSHA 29 CRF 1910.179
CalOSHA	Exempt
Max Overall Height (in.)	139-1/4
Min Overall Height (in.)	109-1/4
Usable I-Beam Length (in.)	96-1/4
Height Adjustable Increments (in.)	6

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=523>