

# Aluminum Adjustable Height Gantry Crane with Phenolic Casters 8 Ft.Wide x 8 Ft. Max Usable Height 6,000 Lb. Capacity Silver

**MODEL AHA-6-8-8**

Overhead Lifting / Adjustable Height Aluminum Gantry Cranes

## PRODUCT OVERVIEW

The adjustable height Aluminum Gantry crane combines lightweight and rigid, sturdy construction into one unit. The all aluminum construction of this gantry crane makes it corrosion resistant and perfect for outdoor use. The lightweight I-beam allows simple height adjustments. All pinned connections make it possible for single person set up and take down in just minutes. Included are two straps, allowing one person to transport the gantry crane in one neat package. Unit comes standard four (4) position locking swivel casters with roller bearings. Locks the rigging in 1 of 4 positions; you can set the wheels and push the gantry crane forward, back, left or right. There is an optional total locking casters that lock the rigging in any position and lo...

## KEY FEATURES

- Heavy-duty welded aluminum construction for long lasting use
- Each unit includes four swivel phenolic casters with four-way position locks for safe positioning
- Easy adjustable height can be done with fork truck or other overhead lifting device
- All units comply with applicable CMAA and ANSI specifications

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**435 lbs**

**ASSEMBLED SIZE**  
**108" W x 96" L x 64.6875" H**

**SHIP WEIGHT**  
**682 lbs**

**PACKAGE 1 SIZE**  
**64" W x 64" D x 18" H**

**COLOR / FINISH**  
**Silver**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Uniform Capacity (lb.)               | 6,000                               |
| Overall I-Beam Length (ft.)          | 8                                   |
| I-Beam Height (In.)                  | 10                                  |
| I-Beam Flange Width (in.)            | 4-11/16                             |
| Under I-Beam Range (in.)             | 74 to 98                            |
| Base Width (in.)                     | 64-11/16                            |
| Caster Quantity/Diameter/Width (in.) | (4) 8 x 3                           |
| Caster Type                          | Swivel (4) Position Locking Casters |
| Caster Material                      | Phenolic                            |
| Caster Top Plate (in.)               | 4 x 4 1/2                           |
| Usable Trolley Travel Distance (in.) | 72-1/4                              |
| Increment Height Adjustment (in.)    | 6                                   |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=522>