

Vinyl-Coated Nylon Dock Seal/Shelter Combination 12 In. 8 Ft. x 10 Ft. Black

MODEL D-150/650-12

Loading Dock Equipment / Dock Seal/Shelter Combinations

PRODUCT OVERVIEW

The Dock Seal/shelter combination is used with a ninety-six (96) inch width by one-hundred twenty (120) inch height door. The top (header) is constructed of wolmanized lumber and is built with a slope to allow for water run-off. It contains a high density foam mounted to treated lumber. The verticals are mounted on wooden boards allowing wall mounted down the length of the vertical pieces. Application with flush dock to building in conjunction with an Edge-O-Dock use a twenty (20) inch projection Dock Seal. Unit is non-returnable.

KEY FEATURES

- Unique two-in-one design provides a dock seal & dock shelter
- Maximum compression design offers the maximum protection
- Built-in air tunnels allow air to escape when contacted by a trailer
- Mounting hardware and installation instructions make installation quick and easy

CORE PRODUCT DATA

ASSEMBLED WEIGHT
206 lbs

ASSEMBLED SIZE
126" W x 12" L x 114" H

SHIP WEIGHT
285 lbs

PACKAGE 1 SIZE
36" W x 120" D x 18" H

COLOR / FINISH
Black

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Projection (in.)	12
Header Width (in.)	114
Header Height (in.)	4
Drop Curtain (in.)	30
Maximum Door Width (in.)	96
Maximum Door Width (ft.)	8
Maximum Door Height (ft.)	10
Usable Door Width (in.)	90
Usable Door Height (in.)	90
Standard Guide Stipe Height (in.)	30
Maximum Compression (in.)	5
Side Width (in.)	12
Side Height (in.)	120
Side Bumper Vinyl-Coated Nylon (oz.)	18
Header Flap Vinyl-Coated Nylon (oz.)	40

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=20>