

Steel Electric Hydraulic Lift Table with Foot Control 24 In. x 48 In. 3000 Lb. Capacity Blue

MODEL EHLT2448-3-43FC

Ergonomic Solutions / Electric Hydraulic Scissor Lift Tables

PRODUCT OVERVIEW

The electric hydraulic scissor lift table with foot control is used by all types of manufacturing and warehouse facilities. The unit lifts products to a desired height creating an ergonomically friendly workspace. The lift table is designed with steel construction for durability and longevity. Additional safety features include a patented pinch point perimeter toe guard to protect pinch points while lowering the table as well as a foot control for lowering and raising the unit. An internal safety velocity fuse is included to maintain platform height in the event of hose or fitting failure. The standard 56 frame electric motor is fully enclosed with additional voltage options available.

KEY FEATURES

- Four-sided electric toe-guard meets OSHA pinch point specification
- Durable aluminum pressure-plated hydraulic pump provides maximum efficiency
- Displacement-style hydraulic cylinders offer maximum strength
- Welded steel construction provides reliable heavy-duty use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
673 lbs

ASSEMBLED SIZE
7" W x 51" L x 24.375" H

SHIP WEIGHT
694 lbs

PACKAGE 1 SIZE
52" W x 30" D x 16" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	3,000
Travel Time (sec.)	16
Vertical Travel (in.)	36
Voltage/Phase	460/3
Hertz	60
Motor Horsepower	2
Hydraulic Component Rating (psi)	3000
Cord Length (in.)	96
Foot Control	24V AC
Raised Height (in.)	43
Lowered Height (in.)	7
Platform Width/Length (in.)	24-3/8 x 48-3/8

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=196>