# Steel Floor Lock 4-3/8 to 5-1/4 In. Height Silver

**MODEL FL-LKL-4**

Facilities Maintenance / Polyurethane Floor Locks



## PRODUCT OVERVIEW

Floor locks are ideal for maintenance and construction facilities. The unit is designed to created a stable environment, while decreasing the chance of jostling or slight movement. The unit is constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

## KEY FEATURES

- Steel construction for durability
- Thermoplastic polyurethane base for stability
- Locking device for quick service
- Lightweight for portability

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**2 lbs** | ASSEMBLED SIZE<br>**3.875" W x 4.375" L x 4.375" H** | SHIP WEIGHT<br>**2 lbs** |
| PACKAGE 1 SIZE<br>**5" W x 5" D x 5" H** | COLOR / FINISH<br>**Silver** | FREIGHT TYPE<br>**Parcel** |

**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**ADDITIONAL PRODUCT VIEWS**





## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Lowered Height (in.)** | 4-3/8 |
| **Raised Height (in.)** | 5-1/4 |
| **Foot Pad Diameter (in.)** | 2-9/16 |
| **Foot Pad Material** | Thermoplastic polyurethane (TPU) |
| **Mounting Plate (in.)** | 3-7/8 x 3-9/16 |
| **Slotted Holes on Center (in.)** | 1-3/4 x 3-1/16 |
| **Mounting Plate Thickness (in.)** | 5/16 |
| **Slotted Mounting Hole Width/Height (in.)** | 3/8 x 1/2 |
| **Inside Bolt Hole Spacing (in.)** | 2-13/16 X 1-3/4 |
| **Outside Bolt Hole Spacing (in.)** | 3-1/16 X 1-3/4 |
| **Suggested Caster Size (in.)** | 4 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **30 Days**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=1067