

# Steel Stationary Hydraulic Drum Dumper 48 In. Dump Height 1,500 Lb. Capacity Blue / Yellow

**MODEL HDD-48-15-S**

Drum Handling Equipment / Hydraulic Drum Dumpers

## PRODUCT OVERVIEW

The Hydraulic drum dumper is what you need to dump heavy drums. Works with plastic, steel, and fiber drums. Dumper has a solid steel chute and all steel construction. Upper travel limit switch, emergency brass safety velocity fuse in cylinder, and vertical adjustment drum restraints are standard. Dumper is operated with a hand held control on a coil cord standard.

## KEY FEATURES

- Internal pre-wired heavy-duty electric motor conveniently dumps drums
- Adjustable drum restraints work with all types of 30 and 55 gallon drums
- Drum rotation design may be stopped at any point
- Solid steel construction offers long lasting reliable use

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**676 lbs**

**ASSEMBLED SIZE**  
**72" W x 71.5" L x 36" H**

**SHIP WEIGHT**  
**814 lbs**

**PACKAGE 1 SIZE**  
**40" W x 64" D x 78" H**

**COLOR / FINISH**  
**Blue (Frame), Yellow (Chute)**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                     |                        |
|-------------------------------------|------------------------|
| Uniform Capacity (lb.)              | 1,500                  |
| Dump Height (in.)                   | 48                     |
| Rotated Height (in.)                | 116                    |
| Level Height (in.)                  | 72                     |
| Accepts                             | 30 and 55-gallon drums |
| Motor Horsepower                    | 3/4                    |
| Single Phase (volts)                | 115                    |
| Motor (Hz)                          | 60                     |
| Power Cord Length (ft.)             | 8                      |
| Hand Held Control Cord Length (ft.) | 8                      |
| Drum Rotation (deg.)                | 135                    |
| Dump Angle (deg.)                   | 45                     |
| Chute Diameter (in.)                | 24                     |
| Raise Time (sec.)                   | 42                     |
| Motor Style                         | 56 Frame               |
| Cylinder Diameter (in.)             | 2-1/2                  |
| Cylinder Length (in.)               | 18                     |
| Chute Reach (in.)                   | 14                     |
| Accepted Drum Diameter (in.)        | 16.5 to 23.5           |
| Accepted Drum Height (in.)          | 27.5 to 39.5           |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=766>