

Steel I-Beam Soft Stop 3 In. Length x 15 In. Width x 5 In. Height 3 In. to 12 In. Usable Yellow

MODEL IBSS-3-12

Overhead Lifting / I-Beam Soft Stop

PRODUCT OVERVIEW

An I-beam soft stop prevents trolleys and items from passing through open ends of I-beams. With an adjustable design the stops can be placed at variable positions along the flange of the I-beam, preventing any possible damage. Built of steel, the stops are a worthwhile addition to the workplace, most notably for the safety of personnel. Due to its basic tension driven design, no mounting holes or permanent alterations are needed!

KEY FEATURES

- Minimizes trolley impact during movement
- Semi-permanent design
- Sold in pairs for complete I-beam protection
- Usable on I-beams widths of 3" to 12"

CORE PRODUCT DATA

ASSEMBLED WEIGHT
7 lbs

ASSEMBLED SIZE
5" W x 13" L x 3" H

SHIP WEIGHT
15 lbs

PACKAGE 1 SIZE
5" W x 12" D x 5" H

COLOR / FINISH
Yellow

FREIGHT TYPE
Parcel

AVAILABILITY Temporarily Unavailable - Please Contact Sales

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Minimum Usable Length (in.)	3
Maximum Usable Length (in.)	12
Overall Width (in.)	2-3/4
Overall Length (in.)	13-1/2
Overall Height (in.)	4
Finish	Powder Coated
Max Usable I-Beam Flange Thickness (in.)	3/4
Maximum Usable Width (in.)	2

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1821>