

# Steel Roll-A-Fold Ladder 58 Degree 4 Perforated 16-13/16 In. Step Width 350 Lb. Capacity Blue

**MODEL LAD-RAF-4-P**

Industrial Ladders / Roll-A-Fold Ladders



## PRODUCT OVERVIEW

Roll-A-Fold ladder, the portable ladder that conveniently folds for storage. Constructed of square tubing framework. Features removable hand railing, deep top platform, perforated steps, and an industrial blue powder coat finish. Unit rolls around on large wheels.

## KEY FEATURES

- Portable ladder design conveniently folds for storage
- Top tread design provides a safe non-slip grip
- Complies with ANSI 14.7 and OSHA 1910.29 specifications
- Heavy-duty formed steel construction offers maximum strength

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**79 lbs**

**ASSEMBLED SIZE**  
**70" W x 41.5" L x 28" H**

**SHIP WEIGHT**  
**117 lbs**

**PACKAGE 1 SIZE**  
**40" W x 60" D x 22" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                     |                |
|-------------------------------------|----------------|
| Uniform Capacity (lb.)              | 350            |
| Hand Rail Height (in.)              | 30             |
| Platform Length (in.)               | 14             |
| Step Width (in.)                    | 16-13/16       |
| Step Depth (in.)                    | 7              |
| Step Spacing (in.)                  | 10             |
| Wheel Quantity/Diameter/Width (in.) | (2) 10 x 2-1/2 |
| Wheel Type                          | Hard Rubber    |
| Step (qty.)                         | 4              |
| Step Angle (degrees)                | 58             |
| Top Step Height (in.)               | 40             |
| Fold Down Length (in.)              | 75             |
| Fold Down Width (in.)               | 30             |
| Fold Down Height (in.)              | 30             |
| Step Type                           | Perforated     |
| OSHA                                | 1910.29        |
| ANSI                                | A14.7          |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=605>