

# Steel High Rise Telescoping Boom 36 In. Fork Pocket Center 4,000 Lb. Capacity Blue

**MODEL LM-HRT-4-36**

Fork Truck Attachments / High Rise Fork Truck Booms



## PRODUCT OVERVIEW

The high rise lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features an infinitely adjustable locking screw alongside a robust safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

## KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**936 lbs**

**ASSEMBLED SIZE**  
**79.8125" W x 54.875" L x 44" H**

**SHIP WEIGHT**  
**936 lbs**

**PACKAGE 1 SIZE**  
**44" W x 80" D x 54" H**

**COLOR / FINISH**  
**Blue (Base Frame)/Yellow**  
**(Extension)**

**FREIGHT TYPE**  
**LTL Loose**

**AVAILABILITY**      Available

**QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                    |                |
|------------------------------------|----------------|
| Uniform Capacity (lb.)             | 4,000          |
| Fork Pocket Center (in.)           | 36             |
| Fork Pocket Width/Height (in.)     | 7-1/2 x 2-1/2  |
| Restraint Length (in.)             | 36             |
| Boom Style                         | Telescoping    |
| Minimum/Maximum Hook Point (in.)   | 30/90          |
| Single-Hook Capacity at 30" (lb.)  | 4000           |
| Single-Hook Capacity at 36" (lb.)  | 3750           |
| Single-Hook Capacity at 42" (lb.)  | 3500           |
| Single-Hook Capacity at 48" (lb.)  | 3250           |
| Single-Hook Capacity at 54" (lb.)  | 3000           |
| Single-Hook Capacity at 60" (lbs.) | 2750           |
| Single-Hook Capacity at 66" (lbs.) | 2500           |
| Single-Hook Capacity at 72" (lbs.) | 2250           |
| Single-Hook Capacity at 78" (lbs.) | 2000           |
| Single-Hook Capacity at 84" (lbs.) | 1750           |
| Single-Hook Capacity at 90" (lbs.) | 1500           |
| Overall Extended Length (in.)      | 92-5/8         |
| Boom Type                          | High Rise Boom |
| OSHA                               | 1910.178(a)(4) |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1777>