

# Steel Quick Lift DC Powered Lift 72 In. Raised Height 400 Lb. Capacity

**MODEL PEL-400S-72-D3**

Ergonomic Solutions / Powered Quick Lifts



## PRODUCT OVERVIEW

The DC powered quick lift is a quiet, lightweight unit used for transport and positioning loads quickly with just the push of the button. The unit is battery operated with a high density polyethylene platform. It features a low profile design for maneuvering in narrow aisles and confined spaces. This quick lift comes with rigid front wheels and swivel rear wheels with locks. The DC system runs with an AC on-board charger. The steel unit has a powder coat blue finish with custom end attachments available.

## KEY FEATURES

- DC powered battery is fast and quiet
- White HDPE platform offers durability and aesthetics
- Chain driven platform operation provides precise positioning
- Touch-pad control allows for easy operation

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**391 lbs**

**ASSEMBLED SIZE**  
**82.25" W x 44.875" L x 24.125" H**

**SHIP WEIGHT**  
**440 lbs**

**PACKAGE 1 SIZE**  
**40" W x 48" D x 90" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                               |                                 |
|-------------------------------|---------------------------------|
| Uniform Capacity (lb.)        | 400                             |
| Lowered Height (in.)          | 6-1/2                           |
| Raised Height (in.)           | 72                              |
| Caster Diameter (in.)         | 4                               |
| Caster Type                   | (2) Rigid (2) Swivel with Brake |
| Caster Material               | Poly-on-Poly                    |
| DC Voltage                    | 24                              |
| AC Charger Voltage            | 115                             |
| Horizontal Load Center (in.)  | 9                               |
| Includes                      | Fully Welded Frame              |
| Handle Length (in.)           | 6                               |
| Platform Length (in.)         | 20                              |
| Platform Thickness (in.)      | 1/2                             |
| Platform Width (in.)          | 24                              |
| Handle Material               | Steel                           |
| Battery Depth                 | 8                               |
| Battery Width                 | 12                              |
| Battery Height                | 7                               |
| Battery Weight                | 48                              |
| Battery Freight Class         | 60                              |
| Battery NMFC Number           | 60700                           |
| Battery NMFC Description      | Gel batteries on unit           |
| Lithium Battery Configuration | C -- Contained In               |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=260>