

Steel Portable Pallet Inverter Low Profile 32 In. to 54 In. Fork Opening 3000 Lb. Capacity Yellow/Black

MODEL PI-P-3000-3254

Ergonomic Solutions / Portable Pallet Inverters

PRODUCT OVERVIEW

Tilt (powered) and rotate (manual) loads with our durable pallet inverter. Low profile design allows the operator to stand on the rider platform and steer the load from workstation to workstation quickly and easily. DC power lift and drive makes operation safe and efficient. The ergonomic handle features easy to operate throttle with infinite forward and reverse speeds, tilt/lower controls, safety belly reverse button, and horn. Features an electromagnetic disc brake with automatic dead-man feature that activates when user releases handle. Includes (4) 6V batteries, an on-board battery charger, battery level gauge, emergency battery disconnect, and horn. Ideal in loading dock areas as a powered pallet truck, powered pallet tilter, or as a manual t...

KEY FEATURES

- Helps improve workplace efficiency
- Large capacity for handling loads both big and small
- Complimentary to a variety of sizes
- Powered lift makes operation safe and efficient

CORE PRODUCT DATA

ASSEMBLED WEIGHT
2070 lbs

ASSEMBLED SIZE
52" W x 99.5" L x 37" H

SHIP WEIGHT
2388 lbs

PACKAGE 1 SIZE
44" W x 96" D x 64" H

COLOR / FINISH
Yellow / Black

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	3,000
Fork Opening (in.)	32 to 54
Fork Width (in.)	6
Fork Length (in.)	35-1/4
Lowered Height (in.)	3-5/8
Turning Radius (in.)	84-1/2
Overall Length (in.)	99-1/2
Overall Width (in.)	37
Overall Height (in.)	52
Use With	Skids Only
Travel Speed - Unloaded (MPH)	2.8
Travel Speed - Loaded (MPH)	2.1
Drive Motor	24V / 1.5 KW
Lift Motor	24V / 2.0 KW
Batteries	(4) 6V / 200 Ah
Battery Charger	24V
Fork Clamping w/o Load	9.5 seconds
Fork Clamping w/ Load	14 seconds
Fork Opening w/o Load	10 seconds
Fork Opening w/ Load	7.5 seconds
Fork Tilting Up w/o Load	15 seconds
Fork Tilting Up w/ Load	23 seconds
Fork Lowering Down w/o Load	14 seconds
Fork Lowering Down w/ Load	13.5 seconds
Battery Depth	22
Battery Width	21
Battery Height	11
Battery Weight	248

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=224>