

# Steel Professional Lever Hoist 10 Ft. Lift Height 6,000 Lb. Capacity Orange

**MODEL PLH-60-10**

Overhead Lifting / Professional Lever Hoists (disc brake)

## PRODUCT OVERVIEW

This versatile professional lever hoist is suitable for lifting, pulling, and lashing the load in many applications. Ideal for confined spaces and can be used at any angle. This lever hoist has a wider hardened ratchet gear, high impact restraint gear case and brake cover. Free wheeling in neutral position serves to quickly attach the load or pull the chain thru the hoist in both directions. With an alloy chain for more strength and less weight. Upper and lower swivel hooks with deformation indicators. Minimum braking load is four (4) times of rated capacity. Fully enclosed brake system. Every unit is issued with an individual test certificate.

## KEY FEATURES

- Alloy steel chain grade 100 offers more strength and less weight
- Tested to one-hundred and fifty (150) percent of the rated capacity
- Manufactured to ISO-9002 quality standards
- Light-weight design is easy to open

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**42 lbs**

**ASSEMBLED SIZE**  
**5" W x 26.5" L x 8" H**

**SHIP WEIGHT**  
**47 lbs**

**PACKAGE 1 SIZE**  
**13" W x 25" D x 13" H**

**COLOR / FINISH**  
**Orange**

**FREIGHT TYPE**  
**Parcel**

**AVAILABILITY** Temporarily Unavailable - Please Contact Sales

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |         |
|--------------------------------------|---------|
| Uniform Capacity (lb.)               | 6,000   |
| Standard Lift (ft.)                  | 10      |
| Minimum Distance Between Hooks (in.) | 22-7/16 |
| Handle Length (in.)                  | 16      |
| Alloy Chain Grade                    | 100     |
| Chain Length (in.)                   | 10      |
| Lever Resistance (lb.)               | 79      |
| Chain Thickness (in.)                | .285    |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=541>