Molded Rubber Wheel Chock with Handle 7-3/8 In. x 15-1/2 In. x 4-7/8 In. Black

MODEL RWC-10-HDL

Loading Dock Equipment / Rubber Wheel Chocks



PRODUCT OVERVIEW

The rubber Wheel Chock with positioning handle is constructed of reinforced rubber to provide a sure grip on virtually any surface. Rubber resists tearing, abrasion, ozone weathering, etc. The functional design is durable in all weather conditions.

KEY FEATURES

- Rubber wheel chock with positioning handle is for ideal operation
- Constructed of reinforced rubber to provide a sure grip on any surface
- Rubber resists tearing, abrasion, ozone weathering, etc
- Functional design is durable in all weather conditions

CORE PRODUCT DATA


ASSEMBLED WEIGHT **12 lbs**	ASSEMBLED SIZE **15.5" W x 7.375" L x 4.875" H**	SHIP WEIGHT **12 lbs**
PACKAGE 1 SIZE **8" W x 11" D x 12" H**	COLOR / FINISH **Black**	FREIGHT TYPE **Parcel**

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS







PRODUCT SPECIFICATIONS

Wheel Chock Connection	None
Wheel Chock Usage	Multi-Purpose
Built-In Handles / Poles	Yes
Grip Surface Material	Rubber
Wheel Chock Quantity	1
Usable Chock Width (in.)	9-1/2
Handle Hole Diameter (in.)	1/2
Handle Length (in.)	5-5/8

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **30 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=79