# Steel Fixed Fork Lift Stacker 62 In. Raised Height 2,000 Lb. Capacity Black / Yellow

**MODEL S-62-FA**

Ergonomic Solutions / Stackers with Powered Drive and Powered Lift



## PRODUCT OVERVIEW

The stacker with powered drive and powered lift is a fully powered electric stacker that transports loads throughout warehouse facilities quickly and with less effort. The high torque drive and lift motor handles heavy-duty jobs. The ergonomic handle features easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. When the proprietary safety-enhancing emergency reverse function is actuated, the emergency reverse belly switch instantly reverses direction and moves the unit forward (away from the operator) until the switch is released or after five seconds have elapsed. The built-in safety circuit will automatically disable the entire uni...

## KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**970 lbs** | ASSEMBLED SIZE<br>**50" W x 67.3125" L x 82.6875" H** | SHIP WEIGHT<br>**1075 lbs** |
| PACKAGE 1 SIZE<br>**64" W x 74" D x 87" H** | COLOR / FINISH<br>**Black / Yellow** | FREIGHT TYPE<br>**LTL Palletized** |

**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**ADDITIONAL PRODUCT VIEWS**







## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 2,000 |
| **Service Range (in.)** | 2-1/2 to 62 |
| **Fork Width/Length (in.)** | 5-9/10 x 42 |
| **Fixed Fork Spacing (in.)** | 26-3/4 (OD) |
| **Adjustable Leg Spacing (in.)** | 38-3/16 to 50 (ID) |
| **Overall Mast Height (in.)** | 82-11/16 |
| **Drive Motor** | DC 24V / 0.7 KW |
| **Lift Motor** | DC 24V / 2.0 KW |
| **Battery** | (2) 12V / 95 Ah |
| **Battery Charger** | DC 24V / 6 amp |
| **Operation Time with Constant Use (hrs.)** | 3 to 4 |
| **Operation Time with Intermittent Use (hrs.)** | 8 |
| **Drive Wheel Qty./Diameter/Width (in.)** | (1) 10 x 3-3/8 |
| **Front Wheel Qty./Diameter/Width (in.)** | (2) 4 x 2.91 |
| **Stabilizer Wheel Qty./Diameter/Width (in.)** | (2) 4 x 2 |
| **Wheel Material** | Poly-on-Steel |
| **Travel Speed - Loaded (MPH)** | 3.1 |
| **Travel Speed - Unloaded (MPH)** | 3.8 |
| **Battery Depth** | 11 |
| **Battery Width** | 14 |
| **Battery Height** | 9 |
| **Battery Weight** | 84 |
| **Battery Freight Class** | 70 |
| **Battery NMFC Number** | 60680 |
| **Battery NMFC Description** | UN2794 BATTERIES WET FILLED WITH ACID |
| **Battery Subclass** | 1 |
| **Lithium Battery Configuration** | C -- Contained In |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=252