

Steel Narrow Mast Stacker DC Powered 43 In. Raised Height Fixed Fork 21 In. Fork Width 3,000 Lb. Capacity Black / Yellow

MODEL SNM3-43-FF-21

Ergonomic Solutions / Narrow Mast Stackers with Powered Drive and Powered Lift

PRODUCT OVERVIEW

The narrow mast stacker is great for the shipping and manufacturing facilities. The stacker provides a fast efficient solution to loading and unloading products in closely confined areas. The stacker features a simple throttle design for lifting control, as well as, infinite forward and reverse speed adjustments. The unit drives on poly on steel steering and load wheels, which provide excellent maneuverability. A battery charger, gauge and horn are included. Models are available with fixed or adjustable forks as well as fixed or adjustable leg supports.

KEY FEATURES

- Emergency reverse belly switch instantly reverses direction
- Stacker is an efficient solution to loading and unloading in closely confined areas
- Throttle design lifts and controls speed adjustments for ideal operation and optimal results
- Includes poly-on-steel wheels for excellent maneuverability and fixed forks for maximum efficiency

CORE PRODUCT DATA

ASSEMBLED WEIGHT
870 lbs

ASSEMBLED SIZE
61" W x 69" L x 31.5" H

SHIP WEIGHT
969 lbs

PACKAGE 1 SIZE
67" W x 85" D x 36" H

COLOR / FINISH
Black / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	3,000
Service Range (in.)	3-3/8 to 43
Fork Width/Length (in.)	4 x 42
Fixed Fork Spacing (in.)	21
Drive Motor	DC 24V / 1.0 KW
Lift Motor	DC 24V / 2.0 KW
Battery	(2) 12V / 80 Ah
Battery Charger	24V / 12 amp
Operation Time with Constant Use (hrs.)	3 to 4
Operation Time with Intermittent Use (hrs.)	8
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=251>