# Aluminum Dock Board Steel Curb 60 In. x 60 In. 15,000 Lb. Capacity Silver

**MODEL TAS-15-6060**

Loading Dock Equipment / Aluminum Truck Dockboards with Steel Safety Curbs



## PRODUCT OVERVIEW

The Aluminum truck dock board with steel safety curbs is designed for portability and safety. The deck is made of tough high strength aluminum tread plate. The edges are beveled for smooth entry and exit. Safety curbs are coated yellow and are constructed of steel with cast tapered ends. Steel legs are bolted on for increased durability. Canted locking legs for easier truck portability. Manufactured in compliance with OSHA. The capacity is based upon the heaviest type of equipment used plus the maximum load carried times the single axle rating of total load. Dynamic loading, driver tendencies, speed and frequency of use must be considered. When using three-wheeled fork trucks order dock board with capacity at least four-times the lifting capacity ...

## KEY FEATURES

- High-strength aluminum tread plate material is durable yet lightweight
- Zinc-plated locking legs are within OSHA compliance
- Beveled entrance and exit edges allow for smoother transition
- Heavy-duty steel curbs are painted yellow and bolted to deck plate for safer use


## CORE PRODUCT DATA


| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**218 lbs** | ASSEMBLED SIZE<br>**60" W x 60" L x 17.6875" H** | SHIP WEIGHT<br>**220 lbs** |
| PACKAGE 1 SIZE<br>**60" W x 60" D x 17" H** | COLOR / FINISH<br>**Silver** | FREIGHT TYPE<br>**LTL Loose** |

**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

### ADDITIONAL PRODUCT VIEWS







## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 15000 |
| **Height Difference at 11 degree/19 percent (in.)** | 10 |
| **Location of Legs From Beveled Edge (in.)** | 11 |
| **Bend Degree** | 11 |
| **Bend Distance from Beveled Edge (in.)** | 8-3/4 |
| **Usable Width (in.)** | 56-1/4 |
| **Usable Length (in.)** | 60 |
| **Plate Thickness (in.)** | 1/2 |
| **Curb Height (in.)** | 4-3/4 |
| **OSHA** | 1910.30(a) |
| **ANSI** | MH 30.2 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=34